



Duradrive Systems International Inc.

250 Rowntree Dairy Road, Woodbridge, Ontario, L4L 9J7

Tel.: 1.866.774.3872 Email: support@drybarrier.com Web: drybarrier.com

Issue Date: November 26, 2014 Rev.: 02

Material Safety Data Sheet

1. Product Information

Product Name: DryBarrier Subfloor
 Product Description & Use: Modular subfloor tile system typically used directly on concrete slabs
 Chemical Composition: Thermoplastic Elastomer
 Colour: Black

2. Hazardous Ingredients / Identity Information

Hazardous Components: None

3. Physical / Chemical Characteristics

Melting Point (Celsius): 120 - 165
 Thermal Decomposition (Celsius): > 300
 Density (g/cm3): 0.950 - 0.990
 Explosion Limits: None
 Hazardous Reactions: None
 Hazardous Decomposition Products (Celsius): > 300 Combustible gas
 Odour: May contain a very mild odour which will dissipate in time

4. Fire & Explosion Hazard Data

Flash Point (Celsius): 350
 Extinguishing Materials: All (Water, Foam, Encapsulating Fire Suppressant, Dry Powder)
 Hazardous Combustion Products: Do not inhale combustion gases
 Unusual Fire & Explosion Hazards: Burns resulting from molten material; Cool with water, do not remove material, see physician

5. Reactivity Data

Stability: Stable at ambient temperature
 Conditions to avoid: Extreme heat or flame

6. Toxicological Properties

None

7. First Aid Measures

None

8. Preventative Measures

Personal Protective Equipment

Respiratory Protection: None
 Hand Protection: Only required during the use of shears or utility knife during installation
 Eye Protection: Only required during the use of shears or utility knife during installation

Storage Requirements: Store under normal conditions

Disposal: 100% recyclable. Code 7

This information and data is based on our knowledge and is intended to describe the product with regard to safety requirements. They are not to be used as property specifications of the product.